



















Daftar Harga Fire Alarm Semi Addressable ASENWARE

Gambar	Nama Produk	Model No.	Keterangan	Harga (Rp.)	Diskon	Harga Setelah Diskon (Rp.)
	Semi Addressable fire alarm control panel (MCFA) 1 Loop	AW-FP101	7" Touchscreen 1 Loop with 250 devices Communication card, include mini Printer and batteries	19,060,000	25%	14,295,000
	Semi Addressable fire alarm control panel (MCFA) 2 Loop	AW-FP102	7" Touchscreen 2 Loop with 500 devices Communication card, include mini Printer and batteries	21,844,000	25%	16,383,000
	Semi Addressable fire alarm control panel (MCFA) 3 Loop	AW-FP103	7" Touchscreen 3 Loop with 750 devices Communication card, include mini Printer and batteries	35,021,600	25%	26,266,200
	Semi Addressable fire alarm control panel (MCFA) 4 Loop	AW-FP104	7" Touchscreen 4 Loop with 1000 devices Communication card, include mini Printer and batteries	37,620,000	25%	28,215,000
	Addressable annunciator	AW-D116	LCD display panel with control buttons	7,980,800	25%	5,985,600
	Addressable power transmitter	AW-D121	Addressable transmitter with 24V 2.5A power supply without battery	8,352,000	25%	6,264,000
	Smoke detector	AW-CSD381	Photo-electric Work voltage: 9-28 VDC Entrance LED output Certificate: LPCB approved	240,120	25%	180,090
	Heat detector	AW-CTD382	Rate of rise 7.1°C/5S A2R Work voltage: 9-28 VDC Certificate: LPCB approved	240,120	25%	180,090
	Heat detector	AW-CTD322	Fix temperature: 60 °C Work voltage: 9-28 VDC	133,632	25%	100,224
	Manual call point	AW-D135C	Working voltage: 24VDC With transparent protection cover, resetable with key	149,640	25%	112,230
	Alarm bell 6 inch	AW-CBL2166-6	Working voltage: 24VDC Alarm Current: ≤60mA Diameter: 6 inch (150mm) Sound level: ≥90dB	240,120	25%	180,090
	Indicator Lamp / flash light	AW-CFL2166	Working Voltage: 24VDC Diameter: 72mm Height: 45mm	174,000	25%	130,500
	Strobe sounder	AW-CSS2166-2	Working Voltage: 20-30VDC Working Current (average): <50mA Flash period: ≤90 times/min Sound Pressure Level: ≥80dB Type of Sound Alarm: 3 Size: 115x134x49mm	274,920	25%	206,190
	Infrared Linear Reflex Beam Smoke Detector with Reflector	AW-BK901	Operating Voltage: 20 V to 28 V DC, Monitor range: 25m, 40m, 70m, 100m, LPCB approved	7,134,000	25%	5,350,500

	Input Module / monitor module	AW-D110	For monitoring the conventional fire alarm devices, like conventional smoke detector	835,200	25%	626,400
	Output Module / control module	AW-D112	For output with 24VDC power supply	1,095,040	25%	821,280
	Supervisory module	AW-D111	For monitoring the relay type equipment status, like pressure switch	835,200	25%	626,400
	Relay module	AW-D113	For output with NO/NC relay	1,143,296	25%	857,472
	Isolator module	AW-D114	Isolate the loop cable every 30 adressable devices	668,160	25%	501,120