

## Heavy foam nozzles

To be operated with foam inductors Z2, Z4 and Z8, recommended working pressure at the inlet is 5 bar. Throw distances 23, 26 and 36 m. Foam coefficient VZ is 5 to 20. Pipe in stainless steel. Protection ring and handle in rubber.

### Heavy foam nozzles, with ball valve shut-off



3601 A

### Storz System Connection or thread



3601 B

Style / Nominal size	Inlet Storz / thread	Mixture flow rate (l / min)	Length (mm)	Width (mm)	Height (mm)	Weight (kg)	Ident-No.	Remarks
S 1	D	100	470	75	113	1,030	60661233	<sup>1)</sup> , Style 3601 B
S 1	G 1 A	100	470	75	113	0,940	60671133	<sup>1)</sup> , Style 3601 B
S 1	M 24 x 2	100	470	75	113	0,950	30002733	<sup>1)</sup> , Style 3601 B
S 2	45	200	748	88	179	2,700	60460133	
S 2	C	200	748	98	184	2,700	10052734	DIN 14 366
S 2	C	200	748	118	194	2,855	10052701	coupling brass
S 2	65	200	748	71	174	2,700	60395134	
S 2	G 2 A	200	866	88	179	2,400	60351434	
S 4	45	400	866	98	184	4,500	60460233	
S 4	C	400	866	118	194	4,400	60313999	
S 4	65	400	866	126	198	4,455	60395234	
S 4	B	400	866	85	174	4,500	10053834	DIN 14 366
S 4	G 2 A	400	866	85	174	4,100	60351534	
S 8	65	800	975	118	194	4,500	60483033	
S 8	B	800	975	126	198	4,500	60278299	DIN 14 366
S 8	G 2 A	800	975	90	179	4,200	10066633	

As per: 17.02.2011