





















PRICELIST ASENWARE Conventional Fire Alarm System






01 June 2022

Photo	Product Name	Model No.	Main Parameters	Unit Price (Rp.)	Discount	Price After Discount (Rp.)
Conventional Fire Alarm System						
	Master Control Fire Alarm (MCFA) / Panel Conventional 1 zone	AW-CFP2166-1	1 fire alarm zone, 2 bell outputs, 1 fire relay, 1 fault relay, metal shell c/w batteries	4.038.000	35%	2.624.700
	Master Control Fire Alarm (MCFA) / Panel Conventional 2 zone	AW-CFP2166-2C	2 fire alarm zones, 2 bell outputs, 1 fire relay, 1 fault relay, plastic front cover ,metal back cover, embedded in wall type c/w batteries	4.626.000	35%	3.006.900
	Master Control Fire Alarm (MCFA) / Panel Conventional 4 zone	AW-CFP2166-4C	4 fire alarm zones, 2 bell outputs, 1 fire relay, 1 fault relay, plastic front cover ,metal back cover, embedded in wall type c/w batteries	5.256.000	35%	3.416.400
	Master Control Fire Alarm (MCFA) / Panel Conventional 6 zone	AW-CFP2166-6C	6 fire alarm zones, 2 bell outputs, 1 fire relay, 1 fault relay, plastic front cover ,metal back cover, embedded in wall type c/w batteries	5.550.000	35%	3.607.500
	Master Control Fire Alarm (MCFA) / Panel Conventional 8 zone	AW-CFP2166-8C	8 fire alarm zones, 2 bell outputs, 1 fire relay, 1 fault relay, plastic front cover ,metal back cover, embedded in wall type c/w batteries	5.844.000	35%	3.798.600
	Master Control Fire Alarm (MCFA) / Panel Conventional 12 zone	AW-CFP2166-12	12 fire alarm zone, 2 bell outputs, 2 fire relay, 1 fault relay, metal shell c/w batteries	10.044.000	35%	6.528.600
	Master Control Fire Alarm (MCFA) / Panel Conventional 16 zone	AW-CFP2166-16	16 fire alarm zone, 2 bell outputs, 2 fire relay, 1 fault relay, metal shell c/w batteries	11.850.000	35%	7.702.500
	Master Control Fire Alarm (MCFA) / Panel Conventional 20 zone	AW-CFP2166-20	20 fire alarm zone, 2 bell outputs, 2 fire relay, 1 fault relay, metal shell c/w batteries	19.248.000	35%	12.511.200
	Master Control Fire Alarm (MCFA) / Panel Conventional 32 zone	AW-CFP2166-32	32 fire alarm zone, 2 bell outputs, 2 fire relay, 1 fault relay, metal shell c/w batteries	25.440.000	35%	16.536.000
	Conventional repeater	AW-CRP2166	32 zone Led indicator, work with 2-32 zone panel via RS485	2.520.000	35%	1.638.000
	GSM module	AW-GSM200	work with fire alarm panel for fire alarm notification by SMS support 4G	3.360.000	35%	2.184.000
	Conventional smoke detector	AW-CSD381	Photo-electric Work voltage: 9-28 VDC Entrance LED output Certificate: LPCB approved	298.200	35%	193.830
	Conventional heat detector	AW-CTD382	Rate of rise 7.1°C/5S A2R Work voltage: 9-28 VDC Certificate: LPCB approved	298.200	35%	193.830
	Conventional smoke and heat detector	AW-CSH831	Multi-detection Work voltage: 9-28 VDC, Entrance LED output	390.600	35%	253.890

	Conventional CO detector	AW-CGD2166C	CO gas detector, Work voltage: 9-28 VDC, relay output	630.000	35%	409.500
	Conventional flame detector	AW-FD602-UV	Parameter: Operating Voltage Range: 12 to 30 VDC Volts Standby Current: ≤10 mA @ 24 VDC Alarm Current: ≤30 mA @ 24 VDC Height:1.8" (45 mm) installed in Base	5.124.000	40%	3.074.400
	Conventional manual call point	AW-D135C	Working voltage: 24VDC With transparent protection cover, resetable with key	231.000	35%	150.150
	Conventional manual push station	AW-CMC2166-6	Working voltage: 9-28VDC Dimensions: 140x105x45mm Resetable with key	453.600	35%	294.840
	Conventional fire bell	AW-CBL2166-6	Working voltage: 24VDC Alarm Current: ≤60mA Diameter: 6 inch (150mm) Sound level: ≥90dB	294.000	35%	191.100
	Conventional fire bell	AW-CBL2166-8	Working voltage: 24VDC Alarm Current: ≤60mA Diameter: 8 inch (200mm) Sound level: ≥100dB	449.400	35%	292.110
	Conventional strobe sounder	AW-CSS2166-2	Working Voltage: 20-30VDC Working Current (average): <50mA Flash period: ≤90 times/min Sound Pressure Level: ≥80dB Type of Sound Alarm: 3 Size: 115x134x49mm	331.800	35%	215.670
	Conventional strobe sounder	AW-CSS2166-3	Working Voltage: 15-30VDC Working Current: ≤30mA Flash period: ≤120 times/min Sound Pressure Level: ≥80dB Type of Sound Alarm: 1 Size: 84x81x56mm	210.000	35%	136.500
	Water proof Conventional strobe sounder	AW-CSS2166-4W	Working Voltage: 12-30VDC Working Current: ≤35mA Flash period: ≤120 times/min Sound Pressure Level: 95 ~ 115dB (Adjustable) Type of Sound Alarm: 8 Size: 125x128x100mm	924.000	35%	600.600
	Conventional flash light	AW-CFL2166	Working Voltage: 24VDC Diameter: 72mm Height: 45mm	210.000	35%	136.500
	Entrance LED indicator	AW-EL102	Working Voltage: 2.5VDC Size: 70.5x36x38mm	151.200	35%	98.280
	Infrared Linear Reflex Beam Smoke Detector with Reflector	AW-BK901	Power supply voltage: 16V-28VDC, Monitor range: 25m, 40m, 70m, 100m Protective area:The maximum protective area of the detector is 1400 m ² and the maximum width is 14m. LPCB approved	8.190.000	35%	5.323.500

	Explosion-proof ultraviolet flame detector	AW-FD706EX	Work voltage: 18V-30VDC Working Current: Monitoring state ≤25mA, Alarm status ≤35mA Flame sensor: 1 UV Explosion-proof: Exp II CT6 Protection: IP66 Temperature range: -40 to 70°C (-40~158°F, Enhance Type)	11.760.000	35%	7.644.000
	Explosion-proof ultraviolet & infrared combined flame detector	AW-FD707EX	Work voltage: 18V-30VDC Working Current: Monitoring state ≤25mA, Alarm status ≤35mA Flame sensor: 1 UV+ 2 IR Explosion-proof: Exp II CT6 Protection: IP66 Temperature range: -40 to 70°C (-40~158°F, Enhance Type)	19.200.000	35%	12.480.000
	Explosion-proof infrared three detector	AW-FD708EX	Work voltage: 18V-30VDC Working Current: Monitoring state ≤25mA, Alarm status ≤35mA Flame sensor: 1 UV+ 2 IR Explosion-proof: Exp II CT6 Protection: IP66 Temperature range: -40 to 70°C (-40~158°F, Enhance Type)	17.280.000	35%	11.232.000
	Linear Heat Cable Per meter	AW-D4068	Indoor using, Alarm threshold of 68°C	92.400	35%	60.060
		AW-D4088	Indoor using, Alarm threshold of 88°C	92.400	35%	60.060
		AW-D4105	Indoor using, Alarm threshold of 105°C	92.400	35%	60.060
		AW-D4068-P	High Performance of Chemical Resistance, Outdoor using, Weather proof, Alarm Threshold of 68°C, Price based on unit of meter.	138.600	35%	90.090
		AW-D4180-P	High Performance of Chemical Resistance, Outdoor using, Weather proof, Alarm Threshold of 180 °C.	176.400	35%	114.660
	Interface Module	AW-D401		2.730.000	35%	1.774.500
	End of line Module	AW-D402		2.730.000	35%	1.774.500
Stand Alone Device and other accessories						
	Fire Resistance Cable (FRC)	AW-FPC2X1.5	2 core x 1.5sqmm + 1 earth wire, per meter	45.000	35%	29.250
		AW-FPC2X2.5	2 core x 2.5sqmm +1 earth wire, per meter	76.800	35%	49.920
	Manual Rotary Hand Fire Alarm Bell	AW-CBL2166-8M	Diameter: 200mm Depth : 140mm Weight : 1.7 kg Materials: Aluminium Volume(dB): 60dB	966.000	35%	627.900
	Water Proof Box for manual call point and manual push station	AW-WB001	Working voltage: 9-28VDC Dimensions: 140x105x45mm Resetable with key Can use for all Asenware brand's manual call point and manual push station	899.850	35%	584.903

Smoke and Heat Detector Tester

	smoke detector tester	AW-D201	length:1.6m*dia 32mm aluminium pole triggering mechanism aluminium case with lock	5.160.000	35%	3.354.000
	heat detector tester	AW-D202	Heating element :220V /100W OR 100V/100W length 1.75m*dia 32mm light weight aluminium pole cable length :30m	6.480.000	35%	4.212.000
	smoke detector sprayer			276.000	35%	179.400
	smoke and heat tester	AW-D206	Smoke detector Temperature Detector 3.5m connection rod is 0.5m/pcs max recommend 5m	21.936.000	35%	14.258.400
	smoke liquid	AW-D207	100ml/pcs detect quantity 5000pcs for AW-D206	547.200	35%	355.680

Keterangan:

1) Harga belum termasuk PPN 11%